Technical datasheet

DIABLO-S-927-1-60-WH

Product description

Diablo is a compact 3-phase LED spotlight with integrated power supply and aluminum heatsink with 50,000 hours lifetime. Available in 3 power options, wide range of color temperatures (2700K-4000K) with CRI 80+/90+. Four light distribution types (15°, 24°, 36°, 60°) and DALI control option available. Ideal for commercial spaces, showrooms and households. 5-year warranty.

LED | 220-240V 50-60Hz | IP20 | CCT 2700 k | CRI 90+

Product technical data

Mains voltage	220 - 240V AC, 50/60Hz
Connection method	3-phase track adapter
Dimming type	Non-dimmable
IP rating	20
Protection class	II
Ambient temperature	0 to +25 °C
Light source	LED
Colour temperature	2700k
Color rendering index	90
Rated luminous flux	1,793 lm
Connected load	13.58 W
Luminous efficacy	132.1 lm/W
Ripple	5 %
Inrush current	7 A
Inrush time	28 µs
Optical system	Lenses
Optical part material	PMMA
Housing material	Die-cast aluminium
Surface finish	Powder coated
Height	132.00 cm
Diameter	90.00 cm
Weight	0.80 kg
Service lifetime (L80 B10)	50 000 h
Warranty	5 years

Dimensions



Light distribution



Optional products

PRO-0410

PRO-0420

PRO-0431L

PRO-0431R

PRO-0432

PRO-0433

PRO-0434

PRO-0437

PRO-04SK

PRO-0610

PRO-0620

PRO-0631L

PRO-0633

PRO-D680-B

PRO-D680-W

PRO-EZ0449

PRO-EZ0450

PRO-M435

PRO-M436

PRO-M438

PRO-MD636L

PRO-MD638