

Technical datasheet

Square12030-L-840-2



Product description

Square 1200x300 is an LED panel with state-of-the-art LED technology and LED source with 50,000 hours lifetime. Available in 3 power options with color temperature 4000K with CRI 80+. Steel body with PMMA diffuser for optimal light distribution and DALI control option available. Fully compatible with existing lighting infrastructure. Ideal for offices, halls and commercial spaces. 5-year warranty.

LED

220-240 V
50-60 Hz

IP20
IP40

UGR
< 19


CCT
4000 k

CRI
80+


Product technical data

| | | | |
|-----------------------|------------------------|----------------------------|---------------|
| Mains voltage | 220 - 240V AC, 50/60Hz | Optical system | Diffuser |
| Connection method | Plug-in terminal | Optical part material | PMMA |
| Dimming type | DALI | Housing material | Steel |
| | | Surface finish | Powder coated |
| IP rating | 40/20 | Width | 295.00 cm |
| Protection class | II | Height | 29.00 cm |
| Ambient temperature | 0 to +30 °C | Length | 1,195.00 cm |
| | | Weight | 1.67 kg |
| Light source | LED | Service lifetime (L80 B10) | 50 000 h |
| Colour temperature | 4000k | Warranty | 5 years |
| Color rendering index | 80 | | |
| Rated luminous flux | 4,800 lm | | |
| Connected load | 30.00 W | | |
| Luminous efficacy | 160.0 lm/W | | |

Dimensions



Light distribution



Optional products

Square Easy
frame

