


Technical datasheet

LINESUR-1696-S-840-1-WH



Product description

LINE Surface is an elegant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser for uniform light. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. DALI control option available. Ideal for offices and commercial spaces. 5-year warranty.



LED

220-240V
50-60Hz

IP20


CCT
4000 k

CRI
80+

Product technical data

Mains voltage	220 - 240V AC, 50/60Hz	Ripple	1 %
Connection method	3-phase track adapter	Inrush current	18 A
Dimming type	Non-dimmable	Inrush time	154 µs
IP rating	20	Optical system	Diffuser
Protection class	I	Optical part material	PMMA
Ambient temperature	0 to +25 °C	Housing material	Aluminium
Light source	LED	Surface finish	Powder coated
Colour temperature	4000k	Width	50.00 cm
Color rendering index	80	Height	70.00 cm
Rated luminous flux	2,263 lm	Length	1,696.00 cm
Connected load	21.32 W	Weight	4.00 kg
Luminous efficacy	106.1 lm/W	Service lifetime (L80 B10)	50 000 h
		Warranty	5 years

Dimensions



Light distribution

