

Technical datasheet

GEMINYM-930-1-WH-



Product description

Geminy linear lamp is designed to create smaller atmospheres within larger spaces. The design features elegant lines and subtle details, along with copper details that complement the structure of the lamp and provide a rich material contrast to powder-coated parts, creating a modern and functional light for any space.

LED

220-240V
50-60Hz

IP20

CE


CCT
3000 k

CRI
90+


Product technical data

Mains voltage	220 - 240V AC, 50/60Hz	Ripple	1 %
Connection method	Plug-in terminal	Inrush current	18 A
Dimming type	Non-dimmable	Inrush time	154 µs
IP rating	20	Optical system	Diffuser
Protection class	I	Optical part material	PMMA
Ambient temperature	0 to +25 °C	Housing material	Steel
Light source	LED	Surface finish	Powder coated
Colour temperature	3000k	Width	40.00 cm
Color rendering index	90	Height	40.00 cm
Rated luminous flux	2,641 lm	Length	1,200.00 cm
Connected load	23.90 W	Weight	4.00 kg
Luminous efficacy	110.5 lm/W	Service lifetime (L80 B10)	50 000 h
		Warranty	5 years

Dimensions



Light distribution



Available cable colors


0111


0900


8765


7953


3119


4867


4906


5305


2166


4406


3358


5474


5744


1257


3119z


0900z


5305z