

Family datasheet

Hexagon Suspended



Product description

The design of the luminaire returns to the power of the basic geometric shapes of the hexagon. By combining several diameters, it is possible to achieve different configurations and lighting scenarios with a great visual impact on the interior.

LED

220-240V
50-60Hz


IP20

CE


Technical description

Mains voltage	220 - 240V AC, 50/60Hz	Optical system	Diffuser
Connection method	Plug-in terminal	Optical part material	PMMA
IP rating	20	Housing material	Aluminium
Protection class	I	Surface finish	Powder coated
Light source	LED	Ambient temperature	0 to +25°C
Switching type	Non-dimmable, DALI	Service lifetime (L80 B10)	50 000h
CRI	80, 90	Warranty	5 years
CCT	3000K, 4000K		
Lumen output	1398-7811 lm		
Efficiency	Up to 109 lm/W		
Power consumption	16-79 W		

Dimensions



Light distribution curves



Available housing colors



Available cable colors



Product codes

The technical specifications of the luminaire are determined through the combination of these attributes, which result in a unique product code.

Order code example: **HEXSUS-1200-L-830-1-BL-**

Attribute	Value	Code
Model	Hexagon Suspended	HEXSUS-
Size	600	600
	1200	1200
	1800	1800
Version	S	S
	M	M
	L	L
CCT	3000k (CRI 80+)	830
	3000k (CRI 90+)	930
	4000k (CRI 80+)	840
	4000k (CRI 90+)	940
Dimming	Non-dimmable	1
	DALI	2
Housing Color	Black	BL
	White	WH
Cable Color	White	0111
	Black	0900
	Gray	8765
	Brown	7953
	Red	3119
	Blue	4867
	Light blue	4906
	Cyan	5305
	Orange	2166
	Purple	4406
	Pink	3358
	Green	5474
	Dark green	5744
	Yellow	1257
	Red/white	3119z
	Black/white	0900z
	Cyan/white	5305z