

Technical datasheet

WORCOM-S-940-1-ASYM-BL



Product description

Worker Compact is a modern track LED luminaire for 3-phase system with LED source with 50,000 hours lifetime. Available in 3 power options, wide range of color temperatures (2700K-4000K) with CRI 80+/90+. Five light distribution types (50°, 80°, ASYM, SYM, WAS) and DALI control option available. Uses the most modern LED technology for powerful and economical lighting. Ideal for offices, corridors and retail spaces. 5-year warranty.

LED

220-240 V  
50-60 Hz

IP20

UGR  
< 19

CCT  
4000 K

CRI  
90+

Product technical data

|                       |                        |                            |               |
|-----------------------|------------------------|----------------------------|---------------|
| Mains voltage         | 220 - 240V AC, 50/60Hz | Ripple                     | 5 %           |
| Connection method     | 3-phase track adapter  | Optical system             | Lenses        |
| Dimming type          | Non-dimmable           | Optical part material      | PMMA          |
|                       |                        | Surface finish             | Powder coated |
| IP rating             | 20                     | Width                      | 43.00 cm      |
| Protection class      | II                     | Height                     | 37.00 cm      |
| Ambient temperature   | 0 to +25 °C            | Length                     | 283.00 cm     |
|                       |                        | Weight                     | 0.45 kg       |
| Light source          | LED                    | Service lifetime (L80 B10) | 50 000 h      |
| Colour temperature    | 4000k                  | Warranty                   | 5 years       |
| Color rendering index | 90                     |                            |               |
| Rated luminous flux   | 761 lm                 |                            |               |
| Connected load        | 9.42 W                 |                            |               |
| Luminous efficacy     | 80.8 lm/W              |                            |               |

Dimensions



Light distribution

