

Technical datasheet

PRIME-6-S-840-1-D-WH



Product description

Prime is a recessed LED downlight with aluminum reflector and LED source with 50,000 hours lifetime. Available in 3 sizes and 3 power options, color temperatures 3000K/4000K with CRI 80+. Three light distribution types (Clear, Diffuse, Partly diffuse) with separate LED driver and DALI control option available. Ideal for offices, commercial spaces and residential buildings. 5-year warranty.



LED

220-240V
50-60Hz

IP20
IP44

CCT
4000 k

CRI
80+

Product technical data

Mains voltage	220 - 240V AC, 50/60Hz
Connection method	Plug-in terminal
Dimming type	Non-dimmable
IP rating	44/20
Protection class	II
Ambient temperature	0 to +30 °C
Light source	LED
Colour temperature	4000k
Color rendering index	80
Rated luminous flux	1,575 lm
Connected load	12.60 W
Luminous efficacy	125.0 lm/W

Optical system	Reflector
Optical part material	Hardened glass
Housing material	Die-cast aluminium
Surface finish	Powder coated
Height	75.00 cm
Diameter	196.00 cm
Weight	0.80 kg
Service lifetime (L80 B10)	50 000 h
Warranty	5 years

Dimensions



Light distribution

