

Technical datasheet

WORDUO-M-940-1-WAS-BL



Product description

Worker Track Duo is a linear LED luminaire for 3-phase track system with LED source with 50,000 hours lifetime. Available in 3 power options, color temperatures 3000K/4000K/5000K with CRI 80+/90+. Five light distribution types (50°, 80°, ASYM, SYM, WAS) with special optics reducing glare and DALI control option available. Provides comfortable and natural lighting with easy track system installation. Ideal for offices and stores. 5-year warranty.

LED

220-240V  
50-60Hz

IP20

UGR  
< 19

CCT  
4000 k

CRI  
90+

Product technical data

|                       |                        |                            |               |
|-----------------------|------------------------|----------------------------|---------------|
| Mains voltage         | 220 - 240V AC, 50/60Hz | Optical system             | Lenses        |
| Connection method     | 3-phase track adapter  | Optical part material      | PMMA          |
| Dimming type          | Non-dimmable           | Housing material           | Aluminium     |
|                       |                        | Surface finish             | Powder coated |
| IP rating             | 20                     | Service lifetime (L80 B10) | 50 000 h      |
| Protection class      | II                     | Warranty                   | 5 years       |
| Ambient temperature   | 0 to +25 °C            |                            |               |
| Light source          | LED                    |                            |               |
| Colour temperature    | 4000k                  |                            |               |
| Color rendering index | 90                     |                            |               |
| Rated luminous flux   | 3,487 lm               |                            |               |
| Connected load        | 33.28 W                |                            |               |
| Luminous efficacy     | 104.8 lm/W             |                            |               |

Dimensions



Light distribution

