

Technical datasheet

WORT-L-830-2-WAS-BL



Product description

Worker Track Duo is a linear LED luminaire for 3-phase track system with LED source with 50,000 hours lifetime. Available in 3 power options, color temperatures 3000K/4000K/5000K with CRI 80+/90+. Five light distribution types (50°, 80°, ASYM, SYM, WAS) with special optics reducing glare and DALI control option available. Provides comfortable and natural lighting with easy track system installation. Ideal for offices and stores. 5-year warranty.

LED

220-240V  
50-60Hz

IP20

UGR  
< 19

CCT  
3000 k

CRI  
80+

Product technical data

|                       |                        |                            |               |
|-----------------------|------------------------|----------------------------|---------------|
| Mains voltage         | 220 - 240V AC, 50/60Hz | Optical system             | Lenses        |
| Connection method     | 3-phase track adapter  | Optical part material      | PMMA          |
| Dimming type          | DALI                   | Housing material           | Aluminium     |
|                       |                        | Surface finish             | Powder coated |
| IP rating             | 20                     | Width                      | 44.00 cm      |
| Protection class      | II                     | Height                     | 53.00 cm      |
| Ambient temperature   | 0 to +25 °C            | Length                     | 1,122.00 cm   |
|                       |                        | Weight                     | 2.80 kg       |
| Light source          | LED                    | Service lifetime (L80 B10) | 50 000 h      |
| Colour temperature    | 3000k                  | Warranty                   | 5 years       |
| Color rendering index | 80                     |                            |               |
| Rated luminous flux   | 4,271 lm               |                            |               |
| Connected load        | 36.54 W                |                            |               |
| Luminous efficacy     | 116.9 lm/W             |                            |               |

Dimensions



Light distribution

