

Family datasheet

Stanley Suspended



Product description

Stanley Suspended is a large pendant LED luminaire with high-quality LED source with 50,000 hours lifetime. Available in 5 sizes (500-1200mm), color temperature 4000K with CRI 80+. Pendant mounting with DALI control option available. Wide range of cable colors. High luminous flux up to 12,169 lm. Ideal for offices and large commercial spaces. 5-year warranty.



LED


220-240V
50-60Hz

IP20


Technical description

Mains voltage	220 - 240V AC, 50/60Hz	Optical system	Diffuser
Connection method	Plug-in terminal	Optical part material	PC
IP rating	20	Housing material	Steel
Protection class	I	Surface finish	Powder coated
Light source	LED	Ambient temperature	0 to +25°C
Switching type	Non-dimmable, DALI	Service lifetime (L80 B10)	50 000h
CRI	80	Warranty	5 years
CCT	4000K		
Lumen output	3042-12169 lm		
Efficiency	Up to 76 lm/W		
Power consumption	40-160 W		

Dimensions



Light distribution curves



Available housing colors



Available cable colors



Product codes

The technical specifications of the luminaire are determined through the combination of these attributes, which result in a unique product code.

Order code example: STYSUS-1000-840-1-BL-

Attribute	Value	Code
Model	Stanley Suspended	STYSUS-
Size	500	500
	600	600
	800	800
	1000	1000
	1200	1200
CCT	4000k (CRI 80+)	840
Dimming	Non-dimmable	1
	DALI	2
Housing Color	Black	BL
	White	WH
Cable Color	White	0111
	Black	0900
	Gray	8765
	Brown	7953
	Red	3119
	Blue	4867
	Light blue	4906
	Cyan	5305
	Orange	2166
	Purple	4406
	Pink	3358
	Green	5474
	Dark green	5744
	Yellow	1257
	Red/white	3119z
	Black/white	0900z
	Cyan/white	5305z